

Manufactured and designed by
Energy Technology and Control Ltd.
Located at
Sussex, United Kingdom

FUNCTIONAL SAFETY CERTIFICATE

Kiwa Gastec Certification hereby declares that the
Parallel Positioning Controller, type

Fireye Inc. PPC6000

and the associated components as detailed in the appendices to this certificate are
suitable for inclusion in a S.I.L. 3 loop.

The compliance is based on an evaluation to EN 61508 (2001).

Report number : 123836

The systems and their associated components only comply with the above listed
safety requirements if the specifications and instructions as detailed in the
commissioning manual are met.

The PPC6100 Parallel Positioning Controller provides fuel air ratio control
systems for industrial burners, providing a PID function to control the
pressure/temperature of the boiler by modulating the fire rate. The controller can
be complemented with various boiler sensors, servo motors, display boards,
oxygen probe interface and daughter boards.

Certificate

Manufactured and designed by
Energy Technology and Control Ltd.
Located at
Sussex, United Kingdom

FUNCTIONAL SAFETY CERTIFICATE

Kiwa Gastec Certification hereby declares that the
Integrated Burner Controller, type

Fireye Inc. Nexus NX6100

and the associated components as detailed in the appendices to this certificate are
suitable for inclusion in a S.I.L. 3 loop.

The compliance is based on an evaluation to EN 61508 (2001).

Report number : 123836

The systems and their associated components only comply with the above listed
safety requirements if the specifications and instructions as detailed in the
commissioning manual are met.

The NX6100 Integrated Burner Controller provides fully integrated burner
control systems for industrial burners, providing a PID function to control the
pressure/temperature of the boiler by modulating the fire rate, full burner
management functions including flame/air pressure monitoring and a fuel shut-
off valve control. The controller can be complemented with various boiler
sensors, servo motors, display boards, oxygen probe interface and daughter
boards.

Where a safety limit function or gas valve proving function is mandatory for the
application, the system shall be included with respectively a Fireye Inc. fail safe
temperature sensor or pressure sensor.


Certificate

GASTEC

Kiwa Gastec Certification
Willemstraat 50
P.O. Box 157
7700 AC APELDOORN
The Netherlands
Tel. +31 55 530105
www.kiwa.com

Number : E 1836 P56

Issued : 9 July 2009


ir. M.L.D. van Rij
Division Director

FUNCTIONAL SAFETY CERTIFICATE: E 1855 FS1 to FS6

Appendix no.: 1

Dated: July 2009

Examination report(s):

123836 dated November 2008

This appendix supersedes appendix no. 1 dated Dec. 2008.

Integrated Burner Controller, type Finyo Inc. Nexus NX6100.

List of all available types:

Model	Characteristics
NX6100	Standard control

List of approved combinations:

Model	Characteristics
NX1021	Gas Pressure Sensor 600mBar
NX1030	Steam Pressure Sensor 25Bar
NX1034	Pressure Sensor (Gas or Steam) 4Bar
NX1040	Boiler Temperature Sensor 0 – 150°C
NX1044	Boiler Temperature Sensor 0 – 400°C
LA220978	Oxygen Probe
LA220979	Oxygen Probe
LA220980	Oxygen Probe
NXC8H	External PSU & CANbus Hub
NXC04	Servo 4Nm
NXC12	Servo 10Nm
NXC20	Servo 20Nm
NXC04A	Servo 4Nm
NXC15A	Servo 15Nm
NXC20A	Servo 20Nm
NXC40	Servo 40Nm
NXC20S	Servo 20Nm
NXC50S	Servo 50Nm
NXDBM0	Daughter Board (comms only)
NXDBI50	Daughter Board (comms + 4-20mA)
NXDBVFD	Daughter Board (comms + inverter interface)
NX8101	Display Unit, 12 key (Basic Function)
NX8110	Display Unit, 12 key (including Relays & RTC)
NX8120	Display Unit, 12 key (including Relays, RTC, Data Logging)
NX02INT	Oxygen Probe interface
NXA7S	Temp Sensor
NXE51120	Servo Interface
NXTSD104	10.4" Touch Screen Display

0063

Page 6 of 6

Appendix no.: 1

Dated: July 2009

Examination report(s):

123636 dated November 2008

FUNCTIONAL SAFETY CERTIFICATE: E 1656 FS1 to FS6

This appendix supersedes appendix no. 1 dated Dec. 2008.

Parallel Positioning Controller, type Freye Inc. PPC0000.

List of all available types:

Model	Characteristics
PPC0000	Standard control

List of approved combinations:

Model	Characteristics
LA220978	Oxygen Probe
LA220979	Oxygen Probe
LA220980	Oxygen Probe
NXC0H	External PSU & CANbus Hub
NXC04	Servo 4Nm
NXC12	Servo 10Nm
NXC20	Servo 20Nm
NXC04A	Servo 4Nm
NXC15A	Servo 15Nm
NXC20A	Servo 20Nm
NXC40	Servo 40Nm
NXC20S	Servo 20Nm
NXC50S	Servo 50Nm
NXD8MB	Daughter Board (comms only)
NXD8IS0	Daughter Board (comms + 4-20mA)
NXD8VFD	Daughter Board (comms + inverter interface)
NX600	Display Unit 9 key (Basic Function)
NX610	Display Unit 9 key (Including Relays & RTC)
NX620	Display Unit 9 key (Including Relays, RTC, Data Logging)
NXC2INT	Oxygen Probe Interface
NXIATS	Temp Sensor
NXES120	Servo Interface
NXTSD104	10.4" Touch Screen Display